## CHAPTER 9H

#### WALL COVERING

### 9H-01. SUBMITTALS

- a. Check for sample color and pattern in accordance with finish schedule requirements on the drawings.
- b. Additional information required from the wall covering manufacturer is as follows:

Installation instructions. Descriptive data Cleaning instructions. Maintenance data.

# 9H-02. MATERIALS

- a. Wall covering shall conform to Federal Standard CCC-W- 408, Type and protective film as specified.
- b. Is wall covering weight as specified? Type indicates weight, as Type I, 7 oz/sy; Type II, 13 oz/sy or Type III, 22 oz/sy.
- $\mbox{\tt d.}$  Is primer and adhesive mildew resistant? Check the container labels.
  - e. Check material type and design of wainscot cap.
  - f. Are exterior corner guards required?
- g. Store well covering flat in a dry location at temperature of not less than  $50\ \mathrm{F}.$

### 9H-03. PREPARATION

- a. Wall surfaces of GWB and plaster shall be clean and dry. Check plaster for not more than 5 percent moisture content before application. Check with a moisture meter.
  - b. Surface shall be within specified smoothness tolerance.

GWB joint and fastener treatment. Sanding rough and glossy surfaces. Coating of primer sealer.

d. Is the minimum temperature of 50 F satisfied in areas to receive wall covering?

## 9H-04. INSTALLATION

- a. Apply as directed in wall covering manufacturer\*s instructions.
- b. Use material in exact order as cut from the roll. Look for special instructions.
- c. When wall cutting (double-cut) procedure is used to match joints, do not cut substrate.
  - d. Do not make joints closer than 6 inches to corners.
- e. Extend wall covering at least  $\frac{1}{2}$  inch behind base, trim, electric plates, etc.
- $\ensuremath{\text{f.}}$  Check pattern and color for match. Should variations occur, corrective action is required.
- g. Finished surfaces shall be free of air pockets, wrinkles, open joints, tears or other defects.